



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **09161640 A**

(43) Date of publication of application: 20 . 06 . 97

(51) Int. Cl.

H01H 61/00**H01H 29/00****H01H 61/01**(21) Application number: **08163401**(22) Date of filing: **24 . 06 . 96**(30) Priority: **13 . 12 . 95 KR 95 9549249**(71) Applicant: **KOREA ELECTRON
TELECOMMUN**(72) Inventor: **BUJYAN CHOI
KYUNHO PAHK
JONHYUN LEE
HEUNG-JHON YU**(54) **LATCHING TYPE HEAT-DRIVEN MICRO-RELAY
ELEMENT**

(57) Abstract:

PROBLEM TO BE SOLVED: To provide an extremely small micro-relay capable of being integrated and having low contact resistance by changing the internal pressure of a storage chamber via a temperature difference, moving a conductive liquid metal in a channel, and closing or opening signal electrodes.

SOLUTION: Power is applied to the heater 12 of an active storage chamber 10 or the heater 42 of a passive storage chamber 40, the internal pressure of the storage chamber is changed by temperature, a liquid metal 50 is moved in a channel 20, and signal electrodes 34, 35 or 31, 32 are closed or opened. When power is selectively applied to the heater 12 or 42, the signal can be turned on or off. This latching heat-driven micro-relay element can be integrated in a silicon wafer bulk by the technique such as macro-burnishing, electroplating, and conductor process, and an extremely small micro-relay capable of being integrated and having small contact resistance can be obtained.

COPYRIGHT: (C)1997 JPO

